




ALFALUX

DECLARATION OF PERFORMANCE		
NO: ECO 01		
DRY- PRESSED CERAMIC TILE, WITH WATER ABSORPTION $0,5\% < E \leq 3\%$ FOR INTERNAL WALLS AND FLOORINGS		
NUOVA RIWAL CERAMICHE SRL , VIA GHIAROLA NUOVA 101, 41042 FIORANO MODENESE (MO) ITALIA		
SYSTEM 4		
Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
_Cadmium	NPD	
_Lead	NPD	
Breaking Strength	>1100 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strenght/adhesion, for:		
Cementitious adhesive, type C2	1N/mm ²	
Thermal Shock Resistance	PASS	
Durability for:		
_ Internal Use:	PASS	
_ External Use: freeze-thaw resistance	NPD	
<p>The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by :</p> <p style="text-align: center;">ALBERTO ALBONETTI (Technical Director)</p> <p style="text-align: center;">Fiorano Modenese 25/06/2013</p> <p style="text-align: right;"></p>		